

COMPLETE CVT FLUID WITH SYNTHETIC LXE TECHNOLOGY

Eliminate the need to stock various OEM fluids with a multi-purpose formulation for use in *any type of CVT transmission.

BENEFITS:

- Provides anti-shudder performance
- Minimises friction between belts and pullets which protects against fatigue damage
- Maintains the performance of a continuously variable transmission by providing excellent wear protection
- Imparts both shear and oxidation stability to the fluid
- Remains fluid at low temperatures for excellent operation in cold weather
- Prevents sludge and varnish build up



FOR USE AS REPLACEMENT FOR THE FOLLOWING OEM CVT FLUIDS

Audi/VW G 052 180 A2
Audi/VW G 052 516 A2
BMW 83 22 0 136 376
BMW 83 22 0 429 154
Daihatsu TC
DEXRON® CVT
Esso CVT EZL 799 (VTF)
Ford CVT WSS-M2C-933-A
Ford CVT23
Ford CVT30

Ford Mercon C
Fujjiyuuko ECVT
Fujjiyuuko ICVT
Genuine Honda CVT
Honda Multimatic Fluid (HMMF)
Hyundai CVTF
Kia CVTF
Mazda CVT Fluid 3320
Mazda TC
Mercedes Benz 236.20

Mercedes Benz CVT 28
MINI Cooper CVT
Mitsubishi Dia Queen CVTF-J1
Mitsubishi Invecs III CVT
Mitsubishi Sportsmode 6 CVT
Mopar® CVT+4 (VTF)
Motorcra! XT-7-QCFT CVTF
Nissan CVT NS
Nissan CVT NS-1 (VTF)
Nissan CVT NS-2 (VTF)

Saturn CVT
Subaru CVTF
Subaru Lineartronic CVTF
Suzuki CVTF 3320
Suzuki CVT Green 1
Suzuki NS-2
Suzuki TC
Toyota TC CVT
ZF CVT VT1

AVAILABILITY

STOCK NO.	UNIT SIZE	CASE WEIGHT/QTY
68112	32 oz.	12.5 lb (6/c)
69450	32 oz. (trilingual)	12.5 lb (6/c)
68232	5 gal.	n/a
68475	55 gal.	n/a

